



Modular range for vans and medium-sized refrigerated vehicles.

PRODUCT SPECIFICATIONS

XARIOS

The XARIOS range is a direct drive refrigeration unit demonstrating unique versatility for vans and trucks. Its design enables transportation of fresh and frozen goods, in single or multi-temperature applications, in vehicles with box volumes from 8 to 48m³ and is available in road only or road and standby versions.

Featuring R404A refrigerant, XARIOS offers a large range of capacities covering temperatures from -20°C to +10°C. Supported by an extensive lineup of ultraslim evaporators, multi-temperature configurations are widely available for multi-product deliveries.

Optimised cost of use

Balancing performance and cost of operation, the XARIOS range offers simple and rapid installation, light weight evaporators to optimise load space and enhanced accessibility for reduced maintenance time.

Driver's comfort

To limit the impact on the community and improve the driver's comfort, the XARIOS range shows low noise levels. Eventually, the cab command is easy to operate and enables an automatic selection of road or road and standby mode.

The units' condensers and evaporator skins are fully recyclable.



Xarios 500 / 600 / 600MT



MXL 1100

Evaporator Range



MXL 1550

Accessories

Road compressor

Road compressor mounting kit

Drain water heater for deep frozen application

Extension connection set for flexible evaporator positioning

Door switch for doors openings Voltage reducer 24 Vdc for trucks

		Capacity (Watts)*		Condenser		Evaporator				
				Weight (kg)		Typo	Weight	Airflow	12 Vdc	24 Vdc
		0°C	-20°C	Road	Standby	Type	(kg)	(m3/h)		
Mono temperature	XARIOS 500	4750	2150	87	154	MXL1100	28	1500	Х	Χ
	XARIOS 600	5500	3000	83	147	MXL1550	42	2100	Х	Χ

^{*} Road capacity at ambient temperature of +30°C (per A.T.P. procedure)

Carrier Airconditioning and Refrigeration Limited.



Tel. Bangalore : 080 - 43442000 Mumbai : 022 - 61700700 Gurgaon : 0124 - 4707311

E-mail: transportservice@carrier.utc.com www.carrierindia.com



^{** 24} Vdc available with Voltage reducer accessory