CITIFRESH™



PRODUCT SPECIFICATIONS

CITIFRESH™

The CITIFRESH unit is a fresh-only direct drive unit. It provides optimum performance with economy, innovation, reliability and ease of installation and use for transporting chilled product. CITIFRESH unit is designed to meet the challenges raised by high ambient temperatures exceeding + 50°C

Using powerful flat evaporator, the unit can support maximum loading capacity for box volumes upto 36m3.





▶ Quick and Easy Installation

very easy for the driver to operate.

► Fresh Application

items and dairy Products.

▶ User friendly Controls

A smaller footprint and easy to install modular concept enables easy installation. Both evaporator and condensers have a four mount arrangement for reduced installation time.

The CITIFRESH unit caters to chilled temperature

requirements of + 4°C to + 22°C and is best suited for

transportation of fruits & vegetables, confectionary

A DIN- type controller provides basic user interface. This can be installed in the vehicle dash board and is


► Low Maintenance

The CITIFRESH unit's streamlined design has very few serviceables parts which, helps to reduce repair and maintenance, resulting in low overall operating cost.

Condenser



Evaporator



▶ Specification table

	Cooling capacity (Watt) Road only	Compressor Capacity (CC)	Refrigerant	Airflow (m³/h)	Dimension (mm) (Width x Height x Depth)		Weight (Kg)	
	+4°C/ +30°C				Evaporator	Condenser	Evaporator	Condenser
CITIFRESH 500	4500	215	R134a	2200	1222 x 278 x 508	1062 x 503 x 534	32	42



Carrier Airconditioning and Refrigeration Limited.

Tel. Bangalore : 080 - 43442000 Mumbai : 022 - 61700700 Gurgaon : 0124 - 4707311

E-mail: transportservice@carrier.utc.com www.carrierindia.com



©2014 Carrier Corporation